


KONYGREEN® AP3500

TECHNICAL SPECIFICATIONS				
PROPERTIES	RESULT	TOLERANCE	UNIT	NOTE
Product properties				
PILE HEIGHT	35	± 10%	mm	
PILE WEIGHT	2,150	± 10%	g/m ²	
TOTAL WEIGHT	3,170	± 10%	g/m ²	
GAUGE	3/8	-	inch/stitches	
PILE MATERIAL	Polyethylene	-	-	
YARN TYPE	Monofilament 9,000 + Crimp 3,500	-	-	
TUFTING NO.	19,000	± 10%	-	
BACK FABRIC	P.P + PET WOVEN	-	-	
BACK COATING	SBR	-	-	
U.V.RAYS	TREATED	-	-	
Roll properties				
Length	On demand	Always delivered with 1% extra		
Width	4.0	-0 + 0.05	m	
Packaging	Rolls are packed individually in green film with KONYGREEN print. Rolls are not on a pallet			

MAIN USAGE	Landscaping
PRODUCTION PLANTS	Kumi-City (Republic of KOREA)
	The product properties are typical values provided by our Internal control system.

STRENGTHS	
<ul style="list-style-type: none"> ▷ Environment-friendly (Heavy metal-free) ▷ High durability (Light Fastness, Abrasion Stability) ▷ Good water permeability. 	

1-23, KOLON TOWER 8F, BYULYANG-DONG, GWACHEON-CITY, GYUNGGI-DO, KOREA
 TEL:(822) 3677-5918/5922 FAX:(822) 3677-5903 E-mail:andykoo@kolon.com/martinpark@kolon.com